

# 9000-628 Specifications

<b>Image sensor:</b>	¼ CCD (HAD), Progressive Scan
<b>Lens</b>	18x (Optical), Motorized under software control F= 4.1 mm (WIDE) to 73.8mm (TELE) F1.4 to F3.0 48 degree (Wide) to 2.8 degree (TELE)
<b>Video S/N</b>	>= 50 db
<b>Shutter Speed</b>	1.1 to 1/10,000s
<b>Input Voltage</b>	DC 12V (DC 10.8 to 13V. Power supply included)
<b>Output Resolution</b>	480 x 640, portrait mode supported
<b>Digital Output Format</b>	USB Compatible, 2.0 & 1.1
<b>Operating Temperature</b>	-20 degrees C to 60 degrees C (-4 degrees F to 140 degrees F)
<b>Dimensions</b>	Video Camera: 132 x 144 x 144 mm (5 ½ x 5 2/3 x 5 2/3 in.) (w/h/d)
<b>Weight</b>	950 g (2 lb 2 oz.)
<b>Integrated Flash</b>	32 levels of flash intensity, guide number 45, Software control
<b>Flash Recharge Time</b>	7 seconds
<b>File Save Format</b>	JPG, BMP, memory, clipboard, Twain
<b>Software Control</b>	Capture, Flash intensity, Live Exposure, Live Color Balance Flash Color Balance Crop Size, Sharpness, Zoom speed, White Balance
<b>System</b>	Includes Camera, internal flash, software and cables
<b>Supported Operating Sys</b>	Win 2K, XP, Vista, Win 7.
<b>Dimensions</b>	63 x 121, 140 mm (w/h/d)
<b>Weight</b>	908 g (32 oz)